

KM-C3130 Specifications

BASIC SPECIFICATIONS:

Configuration:	Digital Color Copier with Standard 250 Sheet Multi-Purpose Drawer, 500 Sheet Universal Drawer, Single Sheet Bypass, Optional Network Printing, Scanning and Internet Fax.
Copy / Scan Resolution:	600 x 600 DPI
Print Resolution:	600 x 1800 DPI
Copier Memory:	Standard 256MB, upgradeable to 512MB
Magnification:	Full Size, 4 Reduction / 4 Enlargement, XY Zoom 2 Custom Zooms, 25 - 400%
Electrical Power Requirements:	120V, 60Hz, 15A
Dimensions:	23.5" W x 31" D x 40.4" H
Weight:	230 lbs
Maximum Monthly Volume:	60,000 Pages Per Month

OUTPUT SPEEDS:

Warm-Up Time:	5 Minutes
First Copy Out (Color / Mono):	9.9 / 7.9 Seconds
Pages Per Minute (Color / Mono):	31 / 31 Letter, 18 / 18 Legal, 15 / 15 Ledger
Continuous Copy:	Up to 999, Auto Reset to 1

IMAGE QUALITY AND VERSATILITY:

Imaging Modes:	Text, Photo, Text & Photo, Printed Image, Map, Copied Image
Additional Features:	Multi-Page Enlargement, Gloss Mode, Image Rotate, Positive / Negative Reverse, Mirror Image, Postcard Mode, Color Separation, Image Repeat
Job Management:	Job Interrupt, Job Build, 10 Job Programs, Job List, Job History, Sample Copy, Priority Job Change, Job Recall, Automatic Job Skip, Watermark Page Numbers Color Adjustments: Auto, TestPrint, Saturation, Portrait, Brightness, Sharpness, Contrast, Hue, Auto / Manual Density, Red, Green, Blue, Color Balance, 20 Monotone Colors, 18 Background Colors, Gradation or Resolution Screen Pattern Settings

PUBLISHING:

Book Mode:	Separation, Spread
Margin Erase:	Center, Frame, Center and Frame
Other Features:	2in1, 4in1, OHP Interleaving

PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Multi-Purpose Drawer (up to 12.25" x 18"), 500 Sheet Universal Drawer (up to 11" x 17"), Single Sheet Bypass (up to 12.25" x 18")
Min / Max Paper Size:	4" x 6" / 12.25" x 18"
Min / Max Paper Capacity:	750 / 3,250 Sheets
Paper Weight:	17 lb Bond - 140 lb Index*
Input Materials:	Plain Paper, Transparencies, Labels, Cardstock, Postcards, Envelopes

PAPER HANDLING OPTIONS:

DUPLIXING DOCUMENT FEEDER: DP-620

Type:	Reversing Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" / 11" x 17"
Capacity:	100 Sheets
Paper Weight:	9 - 55 lb Bond
Dimensions / Weight:	23.07" W x 20.4"D x 5.3"H / 31.3 lbs

AUTOMATIC DUPLEX UNIT: DU-620

Paper Size:	5.5" x 8.5" / 12.25" x 18"
Paper Weight:	17 - 24 lb Bond
Duplex Modes:	1:2, 2:2, 2:1, 2:Book, Book:2

SINGLE POSITION STAPLE FINISHER: DF-620

Stack Capacity:	Main Tray: 1,000 Shets, Sub Tray: 250 Sheets, Optional 3rd Tray: 100 Sheets
Paper Size:	5.5" x 8.5" / 12.25" x 18"
Paper Weight:	17 lb Bond - 140 lb Index
Staple Capacity:	30 Sheets: 8.5" x 11", 15 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	1 Position
Dimensions / Weight:	21.18" W x 25" D x 38.5" H / 78.26 lbs

* 140lb Index can be fed from the Multi-Purpose Drawer loaded with 20 sheets or less, or from the Single Sheet ByPass Tray.

MULTI-POSITION STAPLE BOOKLET FINISHER: DF-625

Stack Capacity:	Main Tray: 1,000 Sheets, Sub Tray: 100 Sheets
Paper Size:	5.5" x 8.5" / 12.25" x 18"
Paper Weight:	17 lb Bond - 140 lb Index
Staple Capacity:	50 Sheets: 8.5" x 11", 25 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	3 Positions: Top Left, Left Side, Top Side
Saddle Stitch & Fold:	8.5" x 11", 11" x 17"; 20 Books (1-5 Sheets), 10 Books (6-10 Sheets)
Punch:	Optional 2 or 3 Hole (PH-620)
Dimensions / Weight:	23.66" W x 23.74" D x 36.73" H / 91.71 lbs

UP TO TWO UNIVERSAL DRAWERS: ST-530

Paper Capacity:	500 Sheets Each
Paper Weight:	17 - 24 lb Bond
Paper Size:	8.5" x 11" - 11" x 17"
Dimensions / Weight:	21.06" W x 22.36" D x 5"H / 18.74 lbs

LARGE CAPACITY DRAWER: PF-620

Paper Capacity:	2,500 Sheets
Paper Weight:	17 - 24 lb Bond
Paper Size:	8.5" x 11"
Dimensions / Weight:	21.06" W x 22.36" D x 11.18" H / 37.48 lbs

PRINT / SCAN SYSTEM: FIERY X3E 31C-M

PRINT:	
Controller:	Embedded: Intel Pentium III / 700 MHz
Printer Memory:	Standard 128MB, Upgradeable to 256MB, Standard 10GB Printer HDD
Supported PDL/Emulations:	Adobe Postscript3, PCL 5C
Fonts:	136 Adobe Type 1, 2 Adobe Master, 45 PCL, 1 Bitmap
Windows™ OS Compatibility:	Windows™ 98/Me/NT4.0/2000/XP
Novell™ OS Compatibility:	Novell NetWare™ 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.6/9.2, 10.x (Classic Mode only)
UNIX OS Compatibility:	Sun OS 4.1.x, Solaris 2.5
Connectivity / Interface:	Standard 10/100 BaseTX, 10Base5, Parallel, Port 9100
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk
Driver:	Fiery X3e 31C-M for Windows, PPD for Mac
Standard Utilities:	Fiery WebTools (WebStatus, WebDownloader, WebSpooler, WebLink, WebSetup, WebInstaller, WebScan, Configure), Installer, EMail Port Monitor, Fiery Netwise, ColorWise Pro Tools, (Calibrator, Color Editor, Profile Manager, Color Setup), Command Workstation, Fiery FreeForm, PDF Printing
Optional Utilities:	DocBuilderPro, EFI Color Profiler, EFI Densitometer

PRINT / SCAN SYSTEM: FIERY S300 31C-M

PRINT:	
Controller:	External: Intel Pentium IV / 2 GHz
Printer Memory:	Standard 256MB, Upgradeable to 1GB, Standard 60GB Printer HDD
Supported PDL/Emulations:	Adobe Postscript3
Fonts:	136 Adobe Type 1, 2 Adobe Master
Windows™ OS Compatibility:	Windows™ 98/Me/NT4.0/2000/XP
Novell™ OS Compatibility:	Novell NetWare™ 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.6/9.x, 10.1 (Classic Mode only), 10.x
UNIX OS Compatibility:	Sun OS 4.1.x, Solaris 2.x
Connectivity / Interface:	Standard 10/100/1000 BaseT, 10Base5, Port 9100
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk
Driver:	Fiery S300 31C-M for Windows, PPD for Mac
Standard Utilities:	Fiery WebTools (WebStatus, WebDownloader, WebSpooler, WebLink, WebSetup, WebInstall, WebScan), Fiery Downloader, Fiery Spooler (Mac only), Command Workstation (PC only), EMail Port Monitor, ColorWise Pro Tools (Calibrator, Color Editor, Profile Manager, Color Setup), PDF Printing
Optional Utilities:	DocBuilderPro, EFI Color Profiler, EFI Densitometer, Graphic Arts Feature Set

SCAN: (included with Fiery X3e 31C-M or Fiery S300 31C-M)	
Resolution:	200, 300, 400, 600 DPI
Color Mode:	Full-Color, GrayScale, Monochrome
Scan Size:	AutoDetect, Custom, Photo: 3" x 5", 4" x 6", 2.25" x 3.25"
File Formats:	PDF, TIFF, JPEG
Supported Protocols:	TCP/IP
Scanning Features:	Fiery Remote Scan (TWAIN), Scan to E-Mail, Scan to MailBox, Scan to Hold Queue, Scan to FTP (X3E 31C-M only)
Standard Utilities:	WebScan
Driver:	TWAIN
INTERNET FAX: (included with Fiery X3e 31C-M)	
Resolution:	200 DPI
Color Mode:	Monochrome
Scan Size:	8.5" x 11", 8.5" x 14", 11" x 17"
File Format:	TIFF

ADDITIONAL OPTIONS: 10GB Hard Disk Drive, Scanner Rack, Copy Table, Copy Desk, Key Counter, 3rd Output Tray for DF-620, Interface Kit for Fiery X3e 31C-M



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2003 Kyocera Mita America, Inc.
www.kyoceramita.com

